# HOT SHOT SERIES GAS, DIRECT DRIVE



4012-10C

# 4GPM@4000PSI



66PPX40GG1Pump

### Standard Accessories

- Gun/wand assembly with insulated grip and quick connects
- 50' high pressure hose w/quick connects
- Maxi-Flo 20%chemical injector assembly w/quick connects
- ◆ 4 color-coded QC spray nozzles
- ◆ 1 color-coded QC chemical nozzle

### Standard Options

- ◆ ATK005 Adjustable Thermostat
- BRK100 Brake Kit
- HRK415 Hose Reel Kit, 150' x 3/8" max. w/ no add'l hose
- MC-B135 Machine Cover Blue Poly Marine Fabric

**NOTE:** AR, CAT, and VIPER gear drive pumps available – consult factory.

## HONDA GX390 Engine

#### Standard Features

- Rugged powder coated steel roll cage frame w/ lifting hook & 13" flat-free tires & threaded axles
- 4-wheel dimensions: 39" L x 31" W x 49" H
- Super efficient schedule 80 coil w/ onepiece molded insulation combustion chamber
- Stainless steel coil wrap
- 8 gallon poly diesel fuel tank w/ fuel filter
- Commercial/Industrial grade engines
- Reliable Beckett burners
- High limit over temp protection
- Safety pressure relief valve
- Thermo-sensor (prevents over heating in bypass mode)

**NOTE:** Gasoline Honda and Diesel powered models include electric start, and battery w/ marine battery box.