HOT SHOT SERIES

GAS, DIRECT DRIVE



4012-42KV

4GPM@4200PSI

VIPER VV4G42G Pump

Standard Accessories

- Gun/wand assembly with insulated grip and quick connects
- ♦ 50′ high pressure hose w/quick connects
- Maxi-Flo 20%chemical injector assembly w/quick connects
- 4 color-coded QC spray nozzles
- ◆ 1 color-coded QC chemical nozzle

Standard Options

- **ATK005** Adjustable Thermostat
- BRK100 Brake Kit
- ◆ HRK415 Hose Reel Kit, 150′ x 3/8″ max. w/no add′l hose
- MC-B135 Machine Cover Blue Poly Marine Fabric

NOTE: AR, CAT, and VIPER gear drive pumps available – consult factory.

CH440Engine

Standard Features

- Rugged powder coated steel roll cage frame w/ lifting hook & 13" flat-free tires & threaded axles
- ♦ 4-wheel dimensions: 39" L x 31" W x 49" H
- Super efficient schedule 80 coil w/ onepiece molded insulation combustion chamber
- Stainless steel coil wrap
- 8 gallon poly diesel fuel tank w/ fuel filter
- ♦ Commercial/Industrial grade engines
- Reliable Beckett burners
- High limit over temp protection
- Safety pressure relief valve
- Thermo-sensor (prevents over heating in bypass mode)

NOTE: Gasoline Honda and Diesel powered models include electric start, and battery w/ marine battery box. Subaru models are manual recoil start.